Method of Control	CORONADO SUBDIVISION E W ↑	Mile	Siding Capacity In Feet	DOB/TGBO	RTC Radio Channel and DTMF Codes
SUBD TRK	ST PAUL JCT	0.0			
	Jct With Vegreville Sub				C8
	GRACE	2.6		2.6	6161
SOO	DUAGH	7.4		1	T2
	GIBBONS	15.6	2330		
	CORONADO	20.6	1360		
	REDWATER	29.6			
	KERENSKY	35.0			
	Jct with Lac La Biche Sub				
	RADWAY	43.2	1650	1	
SUBD TRK	WASKATENAU	49.0		49.0	
	End of Operated Track	50.5			

1 ST PAUL JCT

Anti-Whistling - Except in emergency Rule 14(I) not applicable at Mile 0.64

2 KERENSKY

- (a) Junction switch is in normal position when set for Lac La Biche Sub.
- (b) Track RA50 Speed 10 mph.

3 WASKATENAU

All switches equipped with a lock may be left lined and locked in either position.

4 APPLICABLE ON SUBDIVISION

(a) Heavest car permitted - 268,000 lbs.

Exception: Trains handling cars exceeding 220,000 pounds (including contents) must not exceed:

Mile	MPH	
42.4	Bridge	15
42.6	Bridge	15

(b) Rule 105(a) applicable on subdivision track.

5 SPEEDS

Mile	MPH	
0.0 to 49.0 Z ONE	25	
12.7 то 13.1 Рѕо	10	
19.4 то 19.7 Pso	10	

6 PUBLIC CROSSINGS AT GRADE

Rule 103.1 (d) Applicable to following crossings equipped with push buttons:

Mile 29.51

Governs westward movements and will not function if main track is occupied within 50 feet of crossing. STOP sign erected on elevator track.