WESTWARD TRAINS		Aire			SUSSEX	ast.	в хза	EASTWARD TRAINS				
First	Class				SUBDIVISION S			First	Class	Fourth Class		
615 Passenger	11 Passenger	Miles from Marsh Jct.	Yard Limits	Switching	Atlantic Time	ce Signals	Siding Capacity in feet	12 Passenger	616 Passenger	924 Freight		
Railiner Saily Daily		Mar		Sw	Stations	Office	Sid in f		Railiner	A ITALIA		
2144	1647	0.0	0.11.0	m di	StMARSH JCT. P		of first	1036	1810	ed this.		
	ACKS	2.1	ЭНТО	CINA	SENDP Exit & Entrance Gordon Yard 0.8	iol s	ring tion s 12 s	rsellesi ne for h	ario	Saint u the an		
					GORDON YARD CKWY	NY						
2149	1654	2.9	2.9 4.3	2.9	FUNDY PZ Exit & Entrance Gordon Yard			1030	1804	0130		
f 2156	1701	11.0	10.3 11.8		8.1 SALISBURY Z 4.8		1300	1022	f 1754	0110		
2201	1706	15.8		, , , , , ,	RIVER GLADE		4400	1017	1749	0100		
f 2206	1712	20.6	19.9 21.3	met	Jct. with Havelock SubPETITCODIACZ 15.2	AC	2700	1012	f 1744	0050		
2219	1730	35.8	9 PTIN		PENOBSQUIS	10.00	5930	0958	1730	0025		
s 2230	s 1742	43.3	42.3 44.3		SUSSEXZ	RU	2800	s 0945	s 1709	0005		
f 2243	1757	54.3			NORTON		4450	0930	f 1656	2337		
f 2254	1808	65.0			HAMPTON		1178	0919	f 1646	2317		
2300	1814	70.3			NAUWIGEWAUK		4450	0913	1640	2300		
f 2308	1822	78.2			7.9 ROTHESAY	Live.	milli.w	0905	f 1632	2215		
2315	1830	84.0	81.9	89	COLDBROOKZ.			0857	1625	2200		
s 2330	s 1845 * 1905	86.9	ici Brat	g.x	SAINT JOHNC*KZ	. VR	LOW AS	0845 * 0825	1615	······		
		Cont	ion 14 0	4 Ea	m 925 not applicable between	March	let and	Daily	Daily	Daily		
615	Section 14.0 of Form 835 not applicable between Marsh Jct. and Mileage 2.9.						12	616	924			

SUSSEX SUBDIVISION FOOTNOTES

1 RULE MODIFICATIONS

1.1 CLEARANCES

Movements may be made between Marsh Jct. and mileage 2.9 without authorization of a clearance.

Coldbrook — Fourth class trains must obtain clearance at Saint John and may leave Coldbrook without a clearance.

Saint John — Operators will be on duty at the yard office (Rothesay Ave.) for delivery of train orders and clearances to all trains with the exception of VIA passenger trains.

Operators will be on duty at the VIA station (Mill St. Saint John) in advance of the departure of VIA trains for the purpose of delivering train orders and clearances.

1.2 TRAIN REGISTER MODIFICATIONS

Saint John — * Standard clock, bulletins and train register will be located at the VIA station (Mill St., Saint John) for VIA trains only and at the Yard office (Rothesay Ave.) for all other trains

Conductor of train No. 11 and No. 615 will report arrival time at Saint John, to Train Dispatcher at Moncton.

1.3 CTC SPECIAL FEATURES

The "two tracks" between Marsh Jct. and Bend are designated as "North Track" and "South Track."

(Continued on Page 32)

SUSSEX SUBDIVISION FOOTNOTES

1.4 SPECIAL INSTRUCTIONS APPLY

System 1.8 — At Fundy, Salisbury and Coldbrook

1.5 OTHER MODIFICATIONS

Rule 5 — Saint John — The time of first class trains applies at switch of track G31 located at mileage 86.6.

Rule 5 — *Saint John — The leaving time for No. 11 and the arriving time for No. 12 are for information only and convey no authority on Sussex Sub.

2 **GENERAL FOOTNOTES**

Gordon Yard — When dual control switches in Gordon yard are being hand operated, selector lever must be left in "hand" position until entire movement has passed over the switch.

> Movements may operate at a speed not exceeding 15 miles per hour.

> The engine bell must be rung while moving on any track in the receiving yard.

- 2.2 Salisbury Connection with Albert Subdivision is via siding.
- Penobsquis Crossover switch in siding is to be left set for movement from siding to main track. When in this position, yellow target will so indicate.
- Saint John Connection with CPR McAdam subdivision is via yard track which extends 0.3 miles west of mileage 86.9. Maximum permissible speed on this yard track is 15 miles per

EQUIPMENT RESTRICTIONS 3

- Heaviest engine permitted to operate GF-30c
- 3.2 Heaviest auxiliary permitted 250 tons.
- 3.3 Heaviest car permitted gross weight 263,000

4	SPEEDS				
		M	iles pe	r hour	•
4.1	Mileage	* Railiner	Other Passenger	Freight	
7.1	0.0 to 48.3 zone	75	70	50	
	1.9 Trains and engines using north track at crossing, within 700 feet of crossing (B. O. 103967) until cross-		OTO The T	1.3	
	ing occupied	10	10	10	
	42.3 to 44.0 (B. O. R-27917)	20	20	20	

48.3 to 63.4 zone						70	65	45
63.4 to 66.7 zone						65	60	40
66.7 to 83.5 zone						70	65	45
83.5 to 86.5 zone						30	30	30
86.5 to 86.9 zone						15	15	15

Restrictions in Item 6.1, paragraph (E) of Form 696 not applicable.

5 SPURS AND OTHER TRACKS

Canada Packers Ltd., Mileage 42.5 — Extends north of the main track. Points face east. Capacity 3025 feet.

Maximum permissible speed 20 miles per hour (B. O. R-27917).

5.2 Saint John Freight Track, Mileage 84.0.

Eastward movements do not exceed 10 miles per hour within 400 feet of Ashburn Lake Road crossing until crossing occupied.

5.3 Courtenay Bay Branch (Saint John).

Maximum permissible speed 20 miles per

Do not exceed 10 miles per hour until crossings are fully occupied at the following Public Crossings at Grade: Mileage 0.58 (Hanover Street) and Mileage 0.65 (Brunswick Street).

5.4 Saint John Dry Dock Branch (Saint John).

Maximum permissible speed 20 miles per hour.

Do not exceed 5 miles per hour until crossing is fully occupied at mileage 1.06 (old Irving). Movements over public crossings at grade at Rothesay Avenue and Thorne Avenue must stop and be certain flashing light signals are operating before proceeding over crossing. Push buttons located at crossings.

5.5 Grandview Industrial Park spur (Saint John).

Maximum permissible speed 20 miles per

5.6 McAllister spur (Saint John).

Maximum permissible speed 20 miles per

Movements over all public crossings at grade must be protected by a member of the crew.