

**NORTHWARD TRAINS**

**SOUTHWARD TRAINS**

TRAIN DISPATCHER STANDBY CHANNELS AND TONES		OPR. STANDBY CHANNELS	MTCE. OF WAY LINE-UP CHANNELS	MILES FROM SWAN RIVER	YARD LIMITS	ERWOOD SUBDIVISION STATIONS		OFFICE SIGNALS	SIDING CAPACITY IN FEET
CH3 T1	4			0.0	2.8	SWAN RIVER	CBP WYZ		
				9.8		BOWSMAN		1880	
				21.5	20	BIRCH RIVER		3580	
				30.9		NOVRA		730	
				35.5	41.0	BELLSITE		790	
				42.1		MAFEKING	Z	940	
				45.4	46.6	WHITMORE	YZ	740	
				50.5		BADEN		1020	
				61.0	3	BARROWS		3590	
				66.9		NATIONAL MILLS			
				68.0	20	WESTGATE			
				70.0		ARMIT		940	
				75.4	20	ROSCOE		3590	
				79.9		ERWOOD		1340	
				92.6		HUDSON BAY	Z CKP WY	JC	
CH3 T2	4			99.0/ 100.0					

TRAIN DISPATCHER THE PAS CONTROLS MOVEMENTS

RULES 41 AND 44 APPLICABLE BETWEEN MILEAGE 0.0 AND MILEAGE 100.0  
 MAIN TRACK OF ERWOOD SUB. ENDS AT MILEAGE 100.0  
 RULE 105 APPLIES BETWEEN MILEAGE 100.0 AND MILEAGE 101.1  
 RULE 105A NOT APPLICABLE BETWEEN SWAN RIVER AND MILEAGE 68.0  
 RULES 321 TO 323 APPLICABLE BETWEEN MILEAGE 2.8 AND MILEAGE 68.0

**ERWOOD SUBDIVISION FOOTNOTES**

**1 UNIFORM CODE OF OPERATING RULES**

**1.1 TRAIN REGISTERS**

Hudson Bay—Trains may register by register ticket.

**1.2 SPECIAL INSTRUCTIONS**

System 2.0—Between mileage 2.8 and mileage 68.0.

**2 GENERAL FOOTNOTES**

**2.1 Swan River**—Train and engine crews arriving Swan River will retain MBS Bulletins for return movement.

**2.2 Mafeking**—Train and engine crews arriving Mafeking will retain MBS Bulletins for return movement.

**2.3** Unless authorized by Superintendent, movements must not be operated between Mileage 68.0 and Mileage 99.0.

**2.4 Regulations for the Protection of Track Units and Maintenance Work**  
 Sections 10.0 and 11.0 applicable between Mileage 68.0 and Mileage 100.0.

## ERWOOD SUBDIVISION FOOTNOTES

### 3 EQUIPMENT RESTRICTIONS

Unless authorization received from Office of General Supt. Transportation, the following will apply:

- 3.1 Units in series 2000-3240, 4900-6900, 9300-9317 and 9400-9667 prohibited, except that all units are permitted to operate between Hudson Bay and Mileage 99.0 not exceeding 12 m.p.h.
- 3.2 Heaviest car permitted (including contents): 220,000 lbs.
- 3.3 **Mileage 64.5** (over bridge)  
24 ft. ore cars (loaded) and 250 ton crane prohibited. Maximum speed, 20 m.p.h., when 75 ton cranes are on bridge.  
Maximum speed, 15 m.p.h., when 263,000 lbs freight cars over 40 ft. long are on bridge.  
Maximum speed, 10 m.p.h., when 177,000 lbs. 28 ft. ore cars, 263,000 lbs. freight cars less than 40 feet long, 100 and 120 ton cranes, are on bridge.  
Maximum speed, 5 m.p.h., when 150, 160 and 200 ton cranes are on bridge.

### 4 SPEEDS

4.1 **Mileage 0.0 to 101.1 Zone**

**MILES PER HOUR**  
**All Trains**  
30

- 4.2 **Conditional Speeds**  
**Mileage 0.1** (Main St.)  
Main track movements within 500 feet of crossing until crossing occupied  
**Mileage 9.6** (Fourth St.)  
Southward movements proceeding at less than 10 m.p.h. within 2000 feet of crossing until crossing occupied  
**Mileage 100.9** (Hwy. 109)  
Main track movements within 500 feet of crossing until crossing occupied

10

10

10

### 5 PUBLIC CROSSINGS AT GRADE

- 5.1 **Mileage 0.1** (Main St.)  
General Operating Instructions Item 1.21 applicable.
- 5.2 **Mileage 0.6** (Athlone St.)  
To minimize unnecessary operation of automatic warning devices, southward movement switching south end of spur must leave train north of crossing circuit sign.
- 5.3 **Mileage 9.6** (Fourth St.)  
General Operating Instructions Item 1.21 applicable to southward movements on elevator track.
- 5.4 **Mileage 21.4** (Third St.)  
General Operating Instructions Item 1.21 applicable on elevator track.
- 5.5 **Mileage 100.9** (Highway 109)  
General Operating Instructions Item 1.21 applicable to movements from Turnberry Sub.

### 6 SPURS AND OTHER TRACKS

- 6.1 **Pool Spur ER**  
Mileage 0.7—Extends west of track. Points face north and south. Capacity 2180 feet.
- 6.2 **Dycks Container & Forest Products ER 71**  
Mileage 1.5—Extends west of track. Points face south. Capacity 500 feet.
- 6.3 **Spruce Products Spur ER 81**  
Mileage 1.9—Extends west of track. Points face south. Capacity 570 feet.
- 6.4 **Genstar Ltd. Spur EB 73**  
Mileage 45.3—Extends 8.2 miles east of track off tail of wye.  
Maximum permissible speed 20 m.p.h.  
Protection of impassable track may be provided as prescribed by Rule 41 UCOR.
- 6.5 **Industrial Track EB 87**  
Mileage 66.3—Connected both ends. Capacity 350 feet.
- 6.6 **Simpson and Sask. Forest Spur HZ 01**  
Mileage 100.6—Extends 3.5 miles west of track. Points face south.

	WESTWARD	WESTWARD	WESTWARD	BETWEEN	EASTWARD	EASTWARD	
Car Factor	1090-1076	1300-1399	4206-4399		4206-4399	1300-1399	1090-1076
10	1530			Kelington and Sturge		3700	15
10	1530	2070	7210	Sturge and Thunderhill Jet	0150	2120	10