

YORKTON SUBDIVISION FOOTNOTES

1 UNIFORM CODE OF OPERATING RULES

1.1 SPECIAL INSTRUCTIONS

System 2.0—Between mile-
age 0.9 and mileage 52.5.

2 GENERAL FOOTNOTES

- 2.1 **Yorkton**—Siding located be-
tween south switch and
crossover switch north of
station.

3 INTERLOCKINGS

3.1 Railway Crossing at Grade

CP Rail Mileage 24.8 Automatic
Movements must not exceed 15 m.p.h. when passing
the governing approach signal.
(BTC 92478)

Southward movements occupying approach to
interlocking north of siding south switch longer
than 3 minutes will cause interlocking signal to
indicate STOP, but when movement passes siding
south switch it will indicate PROCEED providing
no movement approaching on conflicting routes.
Northward movements switching Westfair Ltd. Spur
will cause interlocking signal to indicate STOP,
when switch is lined for the spur.

When movement is ready to proceed a member of the
crew must operate push button and interlocking
signal will indicate PROCEED if no conflicting move-
ment. Push button box located at interlocking signal.

Rule 672 applicable.

4 NON-INTERLOCKINGS

- 4.1 Railway crossing at grade Margo Sub. and con-
necting track—the track between Mileage 54.5
Yorkton Sub. and Mileage 0.2 Assiniboine Sub. will
be known as the connecting track.

(RTC R-13735)

5 EQUIPMENT RESTRICTIONS

Unless authorization received from Office of General
Superintendent Transportation, the following will
apply:

5.1 Melville to Mileage 29.5

Units in series 1900-1917, 2500-2559, 3200-3240,
3615-3745, 4400-4601, 5500-5610, 6500-6900,
9300-9317 and units in series 9400-9667 are re-
stricted to 30 m.p.h.

Units in series 2000-2399 and 5000-5399 are restricted
to 12 m.p.h.

5.2 Melville to Margo Jct.

Heaviest car permitted (including contents):
263,000 lbs. but restricted to 30 m.p.h. between
Melville and Mileage 29.5 when exceeding 220,000
lbs.

- 5.3 Designated units must not operate on yard tracks
other than siding at Yorkton. At Canora these units
must not operate on team track, elevator track and
mill track. Reachers must be used when switching on
tracks that designated units must not operate on.


6 SPEEDS

6.1 Mileage

0.0 to 29.5 Zone
29.5 to 54.7 Zone

**MILES
PER HOUR**
All Trains

40
50

NORTHWARD TRAINS	TRAIN DISPATCHER STANDBY CHANNELS AND TONES	MTCE. OF WAY LINE-UP CHANNELS	MILES FROM JCT. WITH RIVERS SUB	YARD LIMITS	YORKTON SUBDIVISION		OFFICE SIGNALS	SIDING CAPACITY IN FEET	SOUTHWARD TRAINS
					STATIONS				
	CH 3 T 2	<div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div>	0.0	↓ 0.9 CANA JCT.	YZ			
					JCT. WITH RIVERS SUB				
			6.1	{ BREWER	P	1890		
					4.9				
			11.0	 MCKIM		1900		
					3.7				
			14.7	 OTTHON	P	1890		
				22.5	{	10.3			
			25.0 YORKTON		PYZ	750		
				10.9					
			35.9 EBENEZER		P	1930		
				6.1					
			42.0 GORLITZ	P	1890			
	6.6								
48.6 BURGIS		1890						
	5.4								
54.0 SOUTH CANORA	Z	1890						
	0.7								
54.7 MARGO JCT.	Z							
		JCT. WITH MARGO SUB							
RULES 41 AND 44 APPLICABLE BETWEEN MILEAGE 0.0 AND 29.5									
RULES 105A NOT APPLICABLE									
RULES 321 TO 323 APPLICABLE BETWEEN MILEAGE 0.9 AND MILEAGE 52.5									

YORKTON SUBDIVISION FOOTNOTES

6.2 Conditional Speeds

	MILES PER HOUR All Trains
--	---------------------------------

Mileage 24.7 (Broadway St.)

Within 500 feet of crossing until crossing occupied

10

Over all public crossings at grade within the limits of the city of Yorkton

10

The limits of the city of Yorkton are:

Between Mileage 23.5 and mileage 26.9

Mileage 54.5 (Prov. Highway 5)

Within 600 feet of crossing until crossing occupied

15

7 PUBLIC CROSSINGS AT GRADE

7.1 Mileage 24.7 (Broadway St.)

To avoid delay to highway traffic northward movements receiving STOP indication, must stop clear of crossing circuit sign located 230 feet south of northward interlocking signal.

When switching is performed at Westfair Ltd. spur, protection will cease to operate.

Subsequent manual clearing of northward interlocking signal will cause protection to start and General Operating Instructions Item 1.21 applicable.

7.2 Mileage 24.9 (Smith Street)

Mileage 54.5 (Highway 5)

General Operating Instructions Item 1.21 applicable from spur.

8 SPURS AND OTHER TRACKS

8.1 Tracks YA 50-59 (Yorkton)

Mileage 25.8—Extends east 2.5 miles.

Maximum permissible speed 10 m.p.h.

General Operating Instructions Item 1.21 applicable.

Heaviest car permitted (including contents):
177,000 lbs.

8.2 Tracks YA 24-36 (Yorkton)

Mileage 25.7 and

Mileage 26.0—Extend west 2.2 miles.

Maximum permissible speed 10 m.p.h.

Heaviest car permitted (including contents):
177,000 lbs.